



**San Joaquin Valley**  
AIR POLLUTION CONTROL DISTRICT



MAR. 23 2015

Mr. Johnathan Le Van  
Aera Energy, LLC  
PO Box 11164  
Bakersfield, CA 93389-1164

**Re: Notice of Minor Title V Permit Modification**  
**District Facility # S-1548**  
**Project # S-1150962**

Dear Mr. Le Van:

Enclosed is the District's analysis of your application for minor Title V permit modification for the facility identified above. You proposed a Title V minor permit modification to incorporate recently issued S-1548-470-6 (under project S-1144413) into the Title V operating permit. The modification authorized an addition of 33 steam-enhanced oil recovery wells to the 63 steam-enhanced wells permitted on PTO S-1548-470.

Enclosed is the engineering evaluation with the following attachments: proposed modified Title V permit, recently issued S-1548-470-6, emission increases, application, and previous Title V permit. This project will be subject to a 45-day EPA commenting period prior to the District taking final action.

If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Thank you for your cooperation in this matter.

Sincerely,

  
Arnaud Marjollet  
Director of Permit Services

Enclosures

cc: Gerardo C. Rios, EPA (w/enclosure) via email

Sayed Sadredin  
Executive Director/Air Pollution Control Officer

Northern Region  
4800 Enterprise Way  
Modesto, CA 95356-8718  
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)  
1990 E. Gettysburg Avenue  
Fresno, CA 93726-0244  
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region  
34946 Flyover Court  
Bakersfield, CA 93308-9725  
Tel: 661-392-5500 FAX: 661-392-5585

## TITLE V APPLICATION REVIEW

Minor Modification

Project #: S1548, 1150962

Engineer: Steve Davidson

Date: March 10, 2015

Facility Number: S-1548

Facility Name: Area Energy, LLC

Mailing Address: PO Box 11164

Bakersfield, CA 93389-1164

*Reviewed by AP Sure Ade*

MAR 11 2015

Contact Name: Jonathan Le Van

Phone: (661) 665-4403

Responsible Official: T.A. Bivens

Title: Process Supervisor

---

### I. PROPOSAL

Area Energy, LLC is proposing a Title V minor permit modification to incorporate Authority to Construct (ATC) #S-1548-470-6 into Area Energy's Title V permit. This ATC authorized an addition of 33 steam-enhanced oil recovery wells to the 30 steam-enhanced wells permitted on PTO S-1548-470 at Area's Light Oil Western Stationary Source. Post-project the total number of wells will be 63.

Conditions will be placed on the permit to ensure the unit meets the requirements of District Rules.

### II. FACILITY LOCATION

The equipment is located in the Belridge oil field, within Area's Light Oil Western stationary source.

### III. EQUIPMENT DESCRIPTION

S-1548-470-7: 63 CYCLIC STEAM ENHANCED WELLS WITH CLOSED CASING VENTS

#### IV. SCOPE OF EPA AND PUBLIC REVIEW

This change to the Title V permit is considered to be a minor modification and, as such, requires no public review.

#### V. APPLICABLE REQUIREMENTS

District Rule 2520, Federally Mandated Operating Permits (Adopted June 21, 2001)

#### VI. DESCRIPTION OF PROPOSED MODIFICATIONS

The Authority to Construct (ATC) permit authorized an addition of 33 steam-enhanced oil recovery wells to the existing 30 steam-enhanced wells permitted on PTO S-1548-470 at Aera's Light Oil Western Stationary Source. Post-project the total number of wells will be 63.

Condition # on PTO S-1548-470-5	Condition # on Propose PTO S-1548-470-7	Condition is New, Modified, or Removed	Reason for Change from Current PTO
2	2	Modified	Total Daily emissions limit raised from 29.3 lb-VOC per day to 31.2 lb-VOC per day
3	3	Modified	Maximum VOC content of the well gas increased from 90% to 95% by weight.

#### VII. COMPLIANCE

In accordance with Rule 2520, 3.20, these modifications:

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;
2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;
4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include;

- a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and
  - b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

Because these permit revisions meet all the above criteria, this is a Minor Modification.

In accordance with Rule 2520, the application meets the procedural requirements of section 11.4 by including;

1. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
2. The source's suggested draft permit; and
3. Certification by a responsible official that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used.

## **VIII. ATTACHMENTS**

- A. Proposed Modified Title V Operating Permit
- B. Authority to Construct
- C. Emissions Increases
- D. Application
- E. Previous Title V Operating Permit

# ATTACHMENT A

Proposed Modified Title V Operating Permit #  
S-1548-470-7

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1548-470-7

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

63 CYCLIC STEAM ENHANCED WELLS WITH CLOSED CASING VENTS

## PERMIT UNIT REQUIREMENTS

1. Cyclic wells covered by this permit shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of these wells. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fugitive emissions from all components associated with this cyclic well operation shall not exceed 31.2 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The VOC content of the well gas shall not exceed 95.0% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All components to be screened shall be identified and categorized according to the following equipment types: connectors, flanges, open-ended lines (sample connections, drains, bleed valves, etc.), pump seals, valves with visible actuators, and other (pressure relief devices, compressor seals, meters, etc.). Components shall be further identified and categorized according to the following types of service: gas/light liquid, light oil, heavy oil, and water/oil. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999). [District Rule 2201] Federally Enforceable Through Title V Permit
6. Flanges shall be monitored with a portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Valves shall be monitored with a portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit
8. All other components such as diaphragms, dump arms, instruments and meters shall be monitored at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain a current list of all cyclic wells associated with this operation, shall update the list whenever a well is added, replaced, or deleted, and such listing shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Permittee shall maintain accurate records of fugitive inspection component counts and calculated fugitive emissions using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c, "Oil and Gas Production Screening Value Ranges Emission Factors" (Feb 1999). Permittee shall make records of component counts, screening values, and calculations readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
12. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
13. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
14. Permittee shall not operate a steam-enhanced crude oil production well unless they comply with one of the following requirements: 1) Permittee shall keep the steam-enhanced crude oil production well vents closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) shall be connected to a VOC collection and control system. The well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere; or 2) Permittee shall install and maintain an APCO-approved VOC collection and control system that is not open to the atmosphere and that is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to an APCO-approved control device that has a VOC destruction or removal efficiency of at least 99%, or that transports gases or vapors back to a process system. [District Rules 2201 and 4401, 5.1.1, and 5.1.2] Federally Enforceable Through Title V Permit
15. During District compliance inspection, the following conditions shall be used to determination of a violation: 1) Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; 2) Existence of a component with a major liquid leak; 3) Existence of a component with a gas leak greater than 50,000 ppmv; or 4) Existence of a component leak consisting of a minor liquid or gas leak, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv, in excess of the allowable number of leaks specified in Table 3 of Rule 4401. [District Rule 4401, 5.2.1] Federally Enforceable Through Title V Permit
16. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
17. Permittee shall keep all hatches closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
18. Except for pipes and unsafe-to-monitor components, permittee shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401, 5.4.1 & 5.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall inspect audio-visually (by hearing and by sight) for leaks all accessible operating pumps, compressors, and pressure relief devices (PRDs) in service at least once each calendar week. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
20. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
21. Permittee shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. Permittee shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
22. Permittee shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
23. Except for PRDs, permittee shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
24. Permittee shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
25. Permittee shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak. The following information shall be included on the tag: 1) the date and time of leak detection; 2) the date and time of leak measurement; 3) leak concentration in ppmv for a gaseous leak; 4) description of whether it is a major liquid leak or a minor liquid leak; and 5) whether the component is an essential component, an unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit
26. Permittee shall keep the tag affixed to the component until all of the following conditions have been met: 1) the leaking component has been repaired or replaced, and 2) the component has been re-inspected using the test methods described in this permit; and 3) the component is found to be in compliance with the requirements of Rule 4401. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit
27. Permittee shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
28. Except for leaking critical components or leaking essential components, if the operator has minimized a leak but the leak still exceeds the applicable leak limits, the operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: 1) repair or replace the leaking component; 2) vent the leaking component to a VOC collection and control system; or 3) remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
29. The leak rate, measured after leak minimization has been performed, shall be used to determine the applicable repair period specified in Table 3 of Rule 4401 and the time of initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401, 5.5.5, and 5.5.6] Federally Enforceable Through Title V Permit
30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
31. Permittee shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.



32. Unless waived by the District, permittee shall maintain source test records which show that the control efficiency requirements of the VOC collection and control system have been satisfied. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
33. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit
34. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit
35. Annual control efficiency compliance tests shall be performed by source testers certified by the California Air Resource Board (CARB) on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive these source testing requirements if the vapor control system does not exhaust to atmosphere, or if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine, or in a smokeless flare. [District Rule 4401, 6.2.1 & 6.2.2] Federally Enforceable Through Title V Permit
36. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit
37. VOC content shall be determined using the latest revision of ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit
38. Permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit
39. VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

40. Permittee shall maintain an inspection log in which, at a minimum, all of the following information shall be recorded for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type; 2) The location, type, and name or description of each leaking component and description of any unit where the leaking component is found; 3) The date of leak detection and the method of leak detection; 4) For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of leaking components; 6) The identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number; and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.1.5 & 6.4] Federally Enforceable Through Title V Permit
41. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401, 6.1.7 & 6.5] Federally Enforceable Through Title V Permit
42. In accordance with the approved OMP, permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
43. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 5.3.3, and 6.7] Federally Enforceable Through Title V Permit
44. All records of required monitoring data and support information required by this permit shall be retained for a period of at least five years and shall be made available for District inspection upon request. [District Rules 2520, 9.4.2, and 4401, 6.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

# ATTACHMENT B

Authority to Construct #  
S-1548-470-6



## AUTHORITY TO CONSTRUCT

**PERMIT NO:** S-1548-470-6

**ISSUANCE DATE:** 01/26/2015

**LEGAL OWNER OR OPERATOR:** AERA ENERGY LLC  
**MAILING ADDRESS:** PO BOX 11164  
BAKERSFIELD, CA 93389-1164

**LOCATION:** LIGHT OIL WESTERN STATIONARY SOURCE  
CA

**SECTION:** 28&29 **TOWNSHIP:** 28S **RANGE:** 21E

**EQUIPMENT DESCRIPTION:**

MODIFICATION OF 30 CYCLIC STEAM ENHANCED WELLS WITH CLOSED CASING VENTS: INCREASE THE NUMBER OF WELLS FROM 30 TO 63

## CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 226 lb, 2nd quarter - 226 lb, 3rd quarter - 226 lb, and fourth quarter - 226 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 4/21/11) for the ERC specified below. [District Rule 2201] Federally Enforceable Through Title V Permit
3. ERC Certificate Number S-4427-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Cyclic wells covered by this permit shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of these wells. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive emissions from all components associated with this cyclic well operation shall not exceed 31.2 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

  
Arnaud Marjollet, Director of Permit Services  
S-1548-470-6 Jan 26 2015 1 31PM -- DAVIDSOS Joint Inspection NOT Required

6. The VOC content of the well gas shall not exceed 95.0% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. All components to be screened shall be identified and categorized according to the following equipment types: connectors, flanges, open-ended lines (sample connections, drains, bleed valves, etc.), pump seals, valves with visible actuators, and other (pressure relief devices, compressor seals, meters, etc.). Components shall be further identified and categorized according to the following types of service: gas/light liquid, light oil, heavy oil, and water/oil. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999). [District Rule 2201] Federally Enforceable Through Title V Permit
9. Flanges shall be monitored with a portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Valves shall be monitored with a portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit
11. All other components such as diaphragms, dump arms, instruments and meters shall be monitored at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Permittee shall maintain a current list of all cyclic wells associated with this operation, shall update the list whenever a well is added, replaced, or deleted, and such listing shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall maintain accurate records of fugitive inspection component counts and calculated fugitive emissions using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c, "Oil and Gas Production Screening Value Ranges Emission Factors" (Feb 1999). Permittee shall make records of component counts, screening values, and calculations readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
14. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
15. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
16. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
17. Permittee shall not operate a steam-enhanced crude oil production well unless they comply with one of the following requirements: 1) Permittee shall keep the steam-enhanced crude oil production well vents closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) shall be connected to a VOC collection and control system. The well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere; or 2) Permittee shall install and maintain an APCO-approved VOC collection and control system that is not open to the atmosphere and that is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to an APCO-approved control device that has a VOC destruction or removal efficiency of at least 99%, or that transports gases or vapors back to a process system. [District Rules 2201 and 4401, 5.1.1, and 5.1.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

18. During District compliance inspection, the following conditions shall be used to determination of a violation: 1) Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; 2) Existence of a component with a major liquid leak; 3) Existence of a component with a gas leak greater than 50,000 ppmv; or 4) Existence of a component leak consisting of a minor liquid or gas leak, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv, in excess of the allowable number of leaks specified in Table 3 of Rule 4401. [District Rule 4401, 5.2.1] Federally Enforceable Through Title V Permit
19. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
20. Permittee shall keep all hatches closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
21. Except for pipes and unsafe-to-monitor components, permittee shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401, 5.4.1 & 5.4.2] Federally Enforceable Through Title V Permit
22. Permittee shall inspect audio-visually (by hearing and by sight) for leaks all accessible operating pumps, compressors, and pressure relief devices (PRDs) in service at least once each calendar week. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
23. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
24. Permittee shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. Permittee shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
25. Permittee shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
26. Except for PRDs, permittee shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
27. Permittee shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
28. Permittee shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak. The following information shall be included on the tag: 1) the date and time of leak detection; 2) the date and time of leak measurement; 3) leak concentration in ppmv for a gaseous leak; 4) description of whether it is a major liquid leak or a minor liquid leak; and 5) whether the component is an essential component, an unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

29. Permittee shall keep the tag affixed to the component until all of the following conditions have been met: 1) the leaking component has been repaired or replaced, and 2) the component has been re-inspected using the test methods described in this permit; and 3) the component is found to be in compliance with the requirements of Rule 4401. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit
30. Permittee shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
31. Except for leaking critical components or leaking essential components, if the operator has minimized a leak but the leak still exceeds the applicable leak limits, the operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: 1) repair or replace the leaking component; 2) vent the leaking component to a VOC collection and control system; or 3) remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
32. The leak rate, measured after leak minimization has been performed, shall be used to determine the applicable repair period specified in Table 3 of Rule 4401 and the time of initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401, 5.5.5, and 5.5.6] Federally Enforceable Through Title V Permit
33. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
34. Permittee shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit
35. Unless waived by the District, permittee shall maintain source test records which show that the control efficiency requirements of the VOC collection and control system have been satisfied. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
36. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit
37. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit
38. Annual control efficiency compliance tests shall be performed by source testers certified by the California Air Resource Board (CARB) on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive these source testing requirements if the vapor control system does not exhaust to atmosphere, or if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine, or in a smokeless flare. [District Rule 4401, 6.2.1 & 6.2.2] Federally Enforceable Through Title V Permit
39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

40. VOC content shall be determined using the latest revision of ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit
41. Permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit
42. VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit
43. Permittee shall maintain an inspection log in which, at a minimum, all of the following information shall be recorded for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type; 2) The location, type, and name or description of each leaking component and description of any unit where the leaking component is found; 3) The date of leak detection and the method of leak detection; 4) For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of leaking components; 6) The identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number; and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.1.5 & 6.4] Federally Enforceable Through Title V Permit
44. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401, 6.1.7 & 6.5] Federally Enforceable Through Title V Permit
45. In accordance with the approved OMP, permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
46. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 5.3.3, and 6.7] Federally-Enforceable Through Title V Permit
47. All records of required monitoring data and support information required by this permit shall be retained for a period of at least five years and shall be made available for District inspection upon request. [District Rules 2520, 9.4.2, and 4401, 6.1] Federally Enforceable Through Title V Permit



# ATTACHMENT C

Emissions Increases

	SSIPE (lb/yr)				
	NOx	VOC	CO	SOx	PM10
S-1548-423	0	694	0	0	0
Total	0	694	0	0	0

# ATTACHMENT D

Application



RECEIVED

MAR 02 2015

SJVAPCD  
Southern Region

February 23, 2015

Mr. Leonard Scandura  
San Joaquin Valley APCD  
1990 East Gettysburg Avenue  
Fresno, CA 93726-0244

**RE: Title V PTO Application – Cyclic Steam Enhanced Wells with Closed Casing Vents (S-1548-470-6)**

Dear Mr. Scandura:

Aera Energy LLC (Aera) requests that the Title V permit for Facility S-1548 be modified to implement Authority to Construct number S-1548-470-6 into the Title V permit.

Enclosed for your review please find the following:

- Application for Title V Modification (TVFORM-008)
- Copy of the Title V Compliance Certification (TVFORM-009).
- Copy of the referenced ATC(s)

Should you have any questions or require additional information please contact Mr. Jonathan Le Van at phone number (661) 665-4403.

Sincerely,

A handwritten signature in cursive script, reading "Jonathan Le Van".

Jonathan Le Van  
Compliance Assurance Specialist  
Attachment(s)

# San Joaquin Valley Air Pollution Control District


## APPLICATION FOR TITLE V MODIFICATION:

RECEIVED

MAR 02 2015

SJVAPCD  
Southern Region

- ☐ ADMINISTRATIVE AMENDMENT  
☒ MINOR MODIFICATION  
☐ SIGNIFICANT MODIFICATION

1. PERMIT TO BE ISSUED TO:		<b>AERA ENERGY LLC</b>	
2. MAILING ADDRESS: STREET/P.O. BOX: CITY: <b>P.O. BOX 11164</b> STATE: <b>CA</b> 9-DIGIT ZIP CODE: <b>93389-1164</b>			
3. LOCATION WHERE THE EQUIPMENT WILL BE OPERATED: STREET: <b>Light Oil Western (S-1548)</b> CITY: <b>Various locations in light oil western</b> <b>Various</b> 1/4 SECTION <b>28&amp;29</b> TOWNSHIP RANGE <b>21E</b>		INSTALLATION DATE:	
4. GENERAL NATURE OF BUSINESS:			
5. Oil and gas production			
6. DO YOU REQUEST A CERTIFICATE OF CONFORMITY WITH THIS ACTION? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO			
7. IS THIS APPLICATION SUBMITTED AS A RESULT OF A NOV/NTC? <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO NOV/NTC No.: _____			
8. SIGNATURE OF APPLICANT/CONTACT PERSON: 		TYPE OR PRINT TITLE OF APPLICANT: <b>Compliance Assurance Specialist</b>	
9. TYPE OR PRINT NAME OF APPLICANT/CONTACT: <b>Jonathan Le Van</b>		DATE: <b>February 23, 2015</b>	
10. FAX NUMBER: <b>(661) 665-7437</b>		TELEPHONE NUMBER: <b>(661) 665-4403</b>	

FOR APCD USE ONLY:

No\$

DATE STAMP	FILING FEE RECEIVED: \$ _____ / DATE PAID: _____ PROJECT NO.: <b>S-1150962</b> FACILITY REGION & ID: <b>S-1548</b>
------------	---

Various

## San Joaquin Valley Unified Air Pollution Control District

Mailing Address: Central Regional Office \* 1990 Gettysburg Avenue \* Fresno, CA 93726-0244 \* (559) 230-5900 \* FAX (559) 230-6061

TVFORM-008

# TITLE V MODIFICATION - COMPLIANCE CERTIFICATION FORM

RECEIVED

## I. TYPE OF PERMIT ACTION (Check appropriate box)

- ☐ SIGNIFICANT PERMIT MODIFICATION      ☐ ADMINISTRATIVE  
☒ MINOR PERMIT MODIFICATION              AMENDMENT

MAR 02 2015

SJVAPCD  
Southern Region

Convert ATC S-1548-470-6 to PTO with operating conditions incorporated into the Title V permit.

COMPANY NAME: <b>AERA ENERGY LLC</b>	FACILITY ID: S-1548
1. Type of Organization: <input checked="" type="checkbox"/> Corporation <input type="checkbox"/> Sole Ownership <input type="checkbox"/> Government <input type="checkbox"/> Partnership <input type="checkbox"/> Utility	
2. Owner's Name: <b>AERA ENERGY LLC</b>	
3. Agent to the Owner: <b>N/A</b>	

## II. COMPLIANCE CERTIFICATION (Read each statement carefully and initial all circles for confirmation):

- ☒ Based on information and belief formed after reasonable inquiry, the source identified in this application will continue to comply with the applicable federal requirement(s) which the source is in compliance.
- ☒ Based on information and belief formed after reasonable inquiry, the source identified in this application will comply with applicable federal requirement(s) that will become effective during the permit term, on a timely basis.
- ☒ Corrected information will be provided to the District when I become aware that incorrect or incomplete information has been submitted.
- ☒ Based on information and belief formed after reasonable inquiry, information and statements in the submitted application package, including all accompanying reports, and required certifications are true, accurate and complete.

I declare, under penalty of perjury under the laws of the state of California, that the forgoing is correct and true:

T. A. Bivens 821866  
Signature of Responsible Official

3-2-15  
Date

T. A. Bivens  
Name of Responsible Official (please print)  
Process Supervisor  
Title of Responsible Official (please print)



## AUTHORITY TO CONSTRUCT

**PERMIT NO:** S-1548-470-6

**ISSUANCE DATE:** 01/26/2015

**LEGAL OWNER OR OPERATOR:** AERA ENERGY LLC  
**MAILING ADDRESS:** PO BOX 11164  
BAKERSFIELD, CA 93389-1164

**LOCATION:** LIGHT OIL WESTERN STATIONARY SOURCE  
CA

**SECTION:** 28&29 **TOWNSHIP:** 28S **RANGE:** 21E

**EQUIPMENT DESCRIPTION:**

MODIFICATION OF 30 CYCLIC STEAM ENHANCED WELLS WITH CLOSED CASING VENTS: INCREASE THE NUMBER OF WELLS FROM 30 TO 63

## CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 226 lb, 2nd quarter - 226 lb, 3rd quarter - 226 lb, and fourth quarter - 226 lb. These amounts include the applicable offset ratio specified in Rule 2201 Section 4.8 (as amended 4/21/11) for the ERC specified below. [District Rule 2201] Federally Enforceable Through Title V Permit
3. ERC Certificate Number S-4427-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Cyclic wells covered by this permit shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of these wells. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive emissions from all components associated with this cyclic well operation shall not exceed 31.2 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

  
Arnaud Marjollet, Director of Permit Services  
S-1548-470-6 Jan 26 2015 1:31PM -- DAVIDSOS Joint Inspection NOT Required

6. The VOC content of the well gas shall not exceed 95.0% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
7. All components to be screened shall be identified and categorized according to the following equipment types: connectors, flanges, open-ended lines (sample connections, drains, bleed valves, etc.), pump seals, valves with visible actuators, and other (pressure relief devices, compressor seals, meters, etc.). Components shall be further identified and categorized according to the following types of service: gas/light liquid, light oil, heavy oil, and water/oil. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999). [District Rule 2201] Federally Enforceable Through Title V Permit
9. Flanges shall be monitored with a portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Valves shall be monitored with a portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit
11. All other components such as diaphragms, dump arms, instruments and meters shall be monitored at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Permittee shall maintain a current list of all cyclic wells associated with this operation, shall update the list whenever a well is added, replaced, or deleted, and such listing shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall maintain accurate records of fugitive inspection component counts and calculated fugitive emissions using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c, "Oil and Gas Production Screening Value Ranges Emission Factors" (Feb 1999). Permittee shall make records of component counts, screening values, and calculations readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
14. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
15. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
16. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
17. Permittee shall not operate a steam-enhanced crude oil production well unless they comply with one of the following requirements: 1) Permittee shall keep the steam-enhanced crude oil production well vents closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) shall be connected to a VOC collection and control system. The well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere; or 2) Permittee shall install and maintain an APCO-approved VOC collection and control system that is not open to the atmosphere and that is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to an APCO-approved control device that has a VOC destruction or removal efficiency of at least 99%, or that transports gases or vapors back to a process system. [District Rules 2201 and 4401, 5.1.1, and 5.1.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE



18. During District compliance inspection, the following conditions shall be used to determination of a violation: 1) Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; 2) Existence of a component with a major liquid leak; 3) Existence of a component with a gas leak greater than 50,000 ppmv; or 4) Existence of a component leak consisting of a minor liquid or gas leak, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv, in excess of the allowable number of leaks specified in Table 3 of Rule 4401. [District Rule 4401, 5.2.1] Federally Enforceable Through Title V Permit
19. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
20. Permittee shall keep all hatches closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
21. Except for pipes and unsafe-to-monitor components, permittee shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401, 5.4.1 & 5.4.2] Federally Enforceable Through Title V Permit
22. Permittee shall inspect audio-visually (by hearing and by sight) for leaks all accessible operating pumps, compressors, and pressure relief devices (PRDs) in service at least once each calendar week. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
23. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
24. Permittee shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. Permittee shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
25. Permittee shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
26. Except for PRDs, permittee shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
27. Permittee shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
28. Permittee shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak. The following information shall be included on the tag: 1) the date and time of leak detection; 2) the date and time of leak measurement; 3) leak concentration in ppmv for a gaseous leak; 4) description of whether it is a major liquid leak or a minor liquid leak; and 5) whether the component is an essential component, an unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

29. Permittee shall keep the tag affixed to the component until all of the following conditions have been met: 1) the leaking component has been repaired or replaced, and 2) the component has been re-inspected using the test methods described in this permit; and 3) the component is found to be in compliance with the requirements of Rule 4401. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit
30. Permittee shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
31. Except for leaking critical components or leaking essential components, if the operator has minimized a leak but the leak still exceeds the applicable leak limits, the operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: 1) repair or replace the leaking component; 2) vent the leaking component to a VOC collection and control system; or 3) remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
32. The leak rate, measured after leak minimization has been performed, shall be used to determine the applicable repair period specified in Table 3 of Rule 4401 and the time of initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401, 5.5.5, and 5.5.6] Federally Enforceable Through Title V Permit
33. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
34. Permittee shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit
35. Unless waived by the District, permittee shall maintain source test records which show that the control efficiency requirements of the VOC collection and control system have been satisfied. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
36. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit
37. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit
38. Annual control efficiency compliance tests shall be performed by source testers certified by the California Air Resource Board (CARB) on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive these source testing requirements if the vapor control system does not exhaust to atmosphere, or if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine, or in a smokeless flare. [District Rule 4401, 6.2.1 & 6.2.2] Federally Enforceable Through Title V Permit
39. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

40. VOC content shall be determined using the latest revision of ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit
41. Permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit
42. VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit
43. Permittee shall maintain an inspection log in which, at a minimum, all of the following information shall be recorded for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type; 2) The location, type, and name or description of each leaking component and description of any unit where the leaking component is found; 3) The date of leak detection and the method of leak detection; 4) For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of leaking components; 6) The identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number; and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.1.5 & 6.4] Federally Enforceable Through Title V Permit
44. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401, 6.1.7 & 6.5] Federally Enforceable Through Title V Permit
45. In accordance with the approved OMP, permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
46. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 5.3.3, and 6.7] Federally Enforceable Through Title V Permit
47. All records of required monitoring data and support information required by this permit shall be retained for a period of at least five years and shall be made available for District inspection upon request. [District Rules 2520, 9.4.2, and 4401, 6.1] Federally Enforceable Through Title V Permit

# ATTACHMENT E

Previous Title V Operating Permit  
S-1548-470-5

# San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** S-1548-470-5

**EXPIRATION DATE:** 05/31/2016

**EQUIPMENT DESCRIPTION:**

30 CYCLIC STEAM ENHANCED WELLS WITH CLOSED CASING VENTS

## PERMIT UNIT REQUIREMENTS

---

1. Cyclic wells covered by this permit shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of these wells. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Fugitive emissions from all components associated with this cyclic well operation shall not exceed 29.3 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The VOC content of the well gas shall not exceed 90.0% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All components to be screened shall be identified and categorized according to the following equipment types: connectors, flanges, open-ended lines (sample connections, drains, bleed valves, etc.), pump seals, valves with visible actuators, and other (pressure relief devices, compressor seals, meters, etc.). Components shall be further identified and categorized according to the following types of service: gas/light liquid, light oil, heavy oil, and water/oil. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Portable hydrocarbon detection instrument shall be operated and calibrated in accordance with recommendations in CAPCOA/CARB's California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities (February, 1999). [District Rule 2201] Federally Enforceable Through Title V Permit
6. Flanges shall be monitored with a portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Valves shall be monitored with a portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit
8. All other components such as diaphragms, dump arms, instruments and meters shall be monitored at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain a current list of all cyclic wells associated with this operation, shall update the list whenever a well is added, replaced, or deleted, and such listing shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Permittee shall maintain accurate records of fugitive inspection component counts and calculated fugitive emissions using CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c, "Oil and Gas Production Screening Value Ranges Emission Factors" (Feb 1999). Permittee shall make records of component counts, screening values, and calculations readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

11. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
12. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401, 3.20] Federally Enforceable Through Title V Permit
13. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0. [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
14. Permittee shall not operate a steam-enhanced crude oil production well unless they comply with one of the following requirements: 1) Permittee shall keep the steam-enhanced crude oil production well vents closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) shall be connected to a VOC collection and control system. The well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere; or 2) Permittee shall install and maintain an APCO-approved VOC collection and control system that is not open to the atmosphere and that is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to an APCO-approved control device that has a VOC destruction or removal efficiency of at least 99%, or that transports gases or vapors back to a process system. [District Rules 2201 and 4401, 5.1.1, and 5.1.2] Federally Enforceable Through Title V Permit
15. During District compliance inspection, the following conditions shall be used to determination of a violation: 1) Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; 2) Existence of a component with a major liquid leak; 3) Existence of a component with a gas leak greater than 50,000 ppmv; or 4) Existence of a component leak consisting of a minor liquid or gas leak, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv, in excess of the allowable number of leaks specified in Table 3 of Rule 4401. [District Rule 4401, 5.6.2] Federally Enforceable Through Title V Permit
16. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
17. Permittee shall keep all hatches closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401, 5.3.2] Federally Enforceable Through Title V Permit
18. Except for pipes and unsafe-to-monitor components, permittee shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401, 5.4.1 & 5.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

19. Permittee shall inspect audio-visually (by hearing and by sight) for leaks all accessible operating pumps, compressors, and pressure relief devices (PRDs) in service at least once each calendar week. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
20. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of Rule 4401 shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401, 5.4.3] Federally Enforceable Through Title V Permit
21. Permittee shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. Permittee shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
22. Permittee shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. [District Rule 4401, 5.4.4] Federally Enforceable Through Title V Permit
23. Except for PRDs, permittee shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
24. Permittee shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401, 5.4.5] Federally Enforceable Through Title V Permit
25. Permittee shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak. The following information shall be included on the tag: 1) the date and time of leak detection; 2) the date and time of leak measurement; 3) leak concentration in ppmv for a gaseous leak; 4) description of whether it is a major liquid leak or a minor liquid leak; and 5) whether the component is an essential component, an unsafe-to-monitor component, or a critical component. [District Rule 4401, 5.5.1] Federally Enforceable Through Title V Permit
26. Permittee shall keep the tag affixed to the component until all of the following conditions have been met: 1) the leaking component has been repaired or replaced, and 2) the component has been re-inspected using the test methods described in this permit; and 3) the component is found to be in compliance with the requirements of Rule 4401. [District Rule 4401, 5.5.2] Federally Enforceable Through Title V Permit
27. Permittee shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401, 5.5.3] Federally Enforceable Through Title V Permit
28. Except for leaking critical components or leaking essential components, if the operator has minimized a leak but the leak still exceeds the applicable leak limits, the operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: 1) repair or replace the leaking component; 2) vent the leaking component to a VOC collection and control system; or 3) remove the leaking component from operation. [District Rule 4401, 5.5.4] Federally Enforceable Through Title V Permit
29. The leak rate, measured after leak minimization has been performed, shall be used to determine the applicable repair period specified in Table 3 of Rule 4401 and the time of initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401, 5.5.5, and 5.5.6] Federally Enforceable Through Title V Permit
30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401, 5.5.7] Federally Enforceable Through Title V Permit
31. Permittee shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.

32. Unless waived by the District, permittee shall maintain source test records which show that the control efficiency requirements of the VOC collection and control system have been satisfied. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
33. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401, 6.1.6] Federally Enforceable Through Title V Permit
34. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401, 6.1.8] Federally Enforceable Through Title V Permit
35. Annual control efficiency compliance tests shall be performed by source testers certified by the California Air Resource Board (CARB) on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive these source testing requirements if the vapor control system does not exhaust to atmosphere, or if all uncondensed VOC emissions collected by the vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine, or in a smokeless flare. [District Rule 4401, 6.2.1 & 6.2.2] Federally Enforceable Through Title V Permit
36. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit
37. VOC content shall be determined using the latest revision of ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by ARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit
38. Permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one centimeter or less from the surface of the component interface. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit
39. VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE  
These terms and conditions are part of the Facility-wide Permit to Operate.



40. Permittee shall maintain an inspection log in which, at a minimum, all of the following information shall be recorded for each inspection performed: 1) The total number of components inspected, and the total number and percentage of leaking components found by component type; 2) The location, type, and name or description of each leaking component and description of any unit where the leaking component is found; 3) The date of leak detection and the method of leak detection; 4) For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of leaking components; 6) The identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 7) The methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number; and 10) The date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401, 6.1.5 & 6.4] Federally Enforceable Through Title V Permit
41. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401, 6.1.7 & 6.5] Federally Enforceable Through Title V Permit
42. In accordance with the approved OMP, permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
43. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401, 5.3.3, and 6.7] Federally Enforceable Through Title V Permit
44. All records of required monitoring data and support information required by this permit shall be retained for a period of at least five years and shall be made available for District inspection upon request. [District Rules 2520, 9.4.2, and 4401, 6.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.